Floor screed conveyors Mixokret M 730



Mixokret M 730

Compact, powerful, convenient. The new hydraulically driven M 730 combines all benefits of the latest Mixokret generation.

The small Mixokret is the ideal pump for small gangs and lightweight vehicles for towing. It is perfect for floor screed but also for fine gravel, sand and fine concretes up to a 16 mm grain size.



Mixokret M 730 – for small gangs, lightweight vehicles and high demands



Thanks to the low weight of the new chassis and the new towing hitch - which can be lowered to 20 cm - the M 730 can also be easily towed by lightweight vehicles.



The analogue instruments are easy to read and intuitive to operate. A durable flap protects the instruments reliably against dirt and damage.



The new water-cooled diesel motor complies with the most recent emission standards (COM III).

Your Putzmeister partner

The M 730 is the starting point in the latest Mixokret generation with many practical features that make your work easier, safer and more profitable.

The new design of the M 730 has a modern and dynamic look. Its durable plastic cover is particularly light and opens extremely wide.

Now you only need to press one button on the hood lock and all the components in the engine compartment are before you within easy reach. This saves time, money and annoyance when doing service work.

A special feature of the M 730 is its powerful hydraulic drive. With this you can stop the mixer shaft when needed or turn it in reverse, to remove a blockage, for example. At the same time, the hydraulic system of the mixing apparatus is protected against overloading.

Moreover, you can now determine the direction in which the lid opens on the newest mixing vessel (on machines without a loader).

All the operating elements and the analogue controls on the M 730 are clearly arranged and easy to understand. This is where the machine operator is provided with all of the important information, such as delivery pressure, oil and system pressure, error lights etc. A newly designed flap provides excellent protection against dirt and damage.

The new water-cooled 3-cylinder diesel engine runs at a very low engine speed. This reduces noise, saves on fuel and minimises wear. At the same time, the M 730 has a high airflow rate.

In addition, the M 730 has wide range of equipment:

- Automatic centralised lubrication system
- Adjustable pressure cut-off
- Lifting eye
- Integrated working lights
- A large tool box

And of course there is also the new DHB version of the M 730 with a hydraulic loader.

If you need a lightweight and inexpensive machine, but do not want to give up power and comfort, then with the M 730 you have a winner.

Technical data

| Output | 2.5 to 3 m³/ h |
|---------------------|--------------------------|
| Delivery pressure | 6 bar |
| Delivery distance* | up to 80 m |
| Delivery height* | up to 45 m |
| Compressor | 2.7 m³/ min |
| Diesel engine | 3-cyl., 24 kW/ 2,300 rpm |
| Mixing volume | 150 |
| Loader volume (op | tion) 150 I |
| Pressure connection | n KKV 89 |
| Weight (DH) | 1,200 kg |
| Weight (DHB) | 1,300 kg |
| L x W x H (DH) | 450 x 150 x 158 cm |
| L x W x H (DHB) | 460 x 150 x 245 cm |

| Part no. M 730 [™] | 111 572.010 |
|-----------------------------|-------------|
| Part no. M 730 DHB | 111 572.020 |

- Plastering machines
- Fine plaster spraying pumps and paint pumps
- Screed pumps
- Professional high-pressure cleaners

Data quoted are empirical values and dependent on the material · Subject to technical changes · © 2007 by Putzmeister Mörtelmaschinen GmbH · All rights reserved (10805 SD) * dependent on the material and the conditions of use