FLEX Elektrowerkzeuge GmbH Bahnhofstrasse 15 D-71711 Steinheim/Murr Phone +49 7144 828-0 Fax +49 7144 25899 info@flex-tools.com www.flex-tools.com

FLEX

Laser measuring technology

ALR 512



The self-levelling rotating laser for vertical and horizontal use

- Full automatic horizontal and vertical self-levelling
- Switchable automatic to manual leveling function in combination with grade mount, obtainable as accessory (order no. 329.479)
- Switchable TILT alarm function: safety modus against unintentional disturbance of the unit
- Two step rotation or target point only
- Incremental manuell angle adjustment up to max ± 5° horizontal and vertical
- Permanent perpendicular beam
- Re-chargable and normal battery operation
- Remote control
- · Automatic switch-off and acoustical signal when limits are exceeded, can be switched off
- Dust- and splash-proof
- · Universal use inside and outside

Order no. 329.452

| Technical attributes | ALR 512 |
|--|------------------------|
| Precision | ± 1 mm/10 m |
| Self-levelling range | ±5° |
| Operation duration with battery drive | 14 h |
| Visible laser diodes | 635 nm |
| Max. range with receiver | 300 m |
| Range rotating (without receiver) | ca. 30 m |
| Range point / scan function (without receiver) | ca. 50 m / ca. 30 m |
| Rotation speed | 500 / 200 rpm |
| Laser class | 2 |
| Weight | 1,70 kg |
| | |

Standard equipment

| Magnetic target panel | 315.281 |
|--|----------|
| Wall and floor mount | 1 piece |
| Conus for wall and floor use | 1 piece |
| 6 V battery pack | 324.159 |
| Mains adapter 6 V | 1 piece |
| Battery container | 1 piece |
| Receiver with dual-display | 1 piece |
| Batteries 1,5 V (AA) | 2 pieces |
| bracket | 1 piece |
| Remote control, incl. 1 battery 9 V | 1 piece |
| Padded carry case | 1 piece |
| | |