

Series IT80M-MC

Standard equipment

- Electric front wheel drive motors
- Negative electromagnetic parking brakes with electric disengagement
- 90° electric steering
- Lateral deck extension 0.36 m
- Manual emergency lowering device
- Cylinder holding valve
- Traction batteries 24V-185Ah C5
- Battery charger with automatic switch-off
- Audible motion alarm, horn, hour meter
- Inclinometer with cut out and alarms
- Mechanical wheel drive release for emergency hauling
- Cushioned non-marking tyres
- Electrical scissor protections
- Pothole protection
- Battery control system with low-voltage cut-out protection
- Overload sensor
- CE - EN 280 marking
- 220V cable predisposition
- Flashing beacon
- Proportional controls with diagnostics

Optional


- 220V cable with plug, socket and safety cut-out

Benefits

- ✓ Electric drive motors: less consumption, longer cycle times
- ✓ Electric steering, unique on the market: reduced environmental impact (No oil required)
- ✓ Parts inter-changability
- ✓ All the components are contained inside the chassis and are easily accessible, nothing remains outside
- ✓ Drivable at full height with lateral deck retracted
- ✓ Excellent speed and gradeability
- ✓ Full capacity allowed on deck extension
- ✓ Sturdy construction and unique design
- ✓ Rigid chassis and scissor pack
- ✓ The lateral deck extension allows for the loading of bulky loads
- ✓ On the IT 4680 MC the 2-door gate makes it easier to load and unload bulky materials




All the component parts are easily accessible for servicing.





IT 4680M



IT 4680 M - IT 4680 MC

Number of scissors		3
A	mm	4500
B	mm	6500
C (Pot-hole raised/lowered)	mm	88 / 21
D	mm	2014
E	mm	858
Capacity (including 2 people)	kg	250
Electric drive motors	V/kW	24/2,4
Lifting power pack – hydraulic type	V/kW	24/2,1
Traction battery	V/Ah	24/185 c5
Battery weight	kg	4x28
Battery charger	V/A	24/20
Oil tank capacity	l	7
Traction speed	km/h	0 ÷ 4
Safety traction speed	km/h	0,7
Gradeability	%	25
Internal steering radius	m	0
External steering radius	m	1,65
Tyre dimensions	mm	315x100
Tyre type		cushion
Max side/longitudinal tilt angle	degrees	1,5/3
Total weight	kg	1470

